

# ACCESSORIES



VB SERIES, VACUUM BREAKERS				
SIZE (NPT)	MODEL NUMBER	SHIP WGT.		
		Lbs./(kg)		
1/2"	VB-5	1 (.5)		

Recommended for all fluoropolymer heat exchangers used with steam service.

# **VB Series Features and Benefits**

#### **STEAM HEATING APPLICATIONS:**

 Protects fluoropolymer heat exchangers from collapse damage due to vacuum conditions that often occur in steam lines.

#### **RUGGED CONSTRUCTION:**

 Brass body with stainless steel operating mechanism and EPR O-ring seat.


### EASY INSTALLATION.


### CAPACITIES:

- ♦ ½-inch FNPT only.
- Maximum steam service: 50 PSIG.
- Maximum temperature rating: 365°F (185°C).
- Can be installed in any position.

**NOTE:** One vacuum breaker should be installed immediately downstream from each fluoropolymer heat exchanger in the system.

## DIMENSIONS





## VACUUM BREAKER ORDERING INFORMATION

Series		Size (NPT)	
VB	] [	-5 = 1/2"	

## **ORDERING EXAMPLE:**

VB-5 Vacuum breaker, ½" NPT.



7010 Lindsay Dr. • Mentor, OH 44060 USA • USA/CAN: 800-621-1998 • 440-974-1300 • Fax: 440-974-9561 www.processtechnology.com • E-mail: info@process-technology.com